

Discount Code update 3.1 for osCommerce 2.2

1. Perform the SQL query to your osCommerce database.

```
ALTER TABLE `discount_codes` ADD `exclude_specials` TINYINT( 1 ) NOT NULL AFTER `order_info` ;
```

2. Overwrite existing files with files from the catalog/ folder:

```
catalog/admin/discount_codes.php  
catalog/admin/includes/languages/english/discount_codes.php  
catalog/discount_code.php  
catalog/ext/jquery/jquery-1.4.2.min.js  
catalog/images/icons/dc_failed.gif  
catalog/images/icons/dc_progress.gif  
catalog/images/icons/dc_success.gif  
catalog/includes/modules/order_total/ot_discount.php
```

3. Modify the catalog/checkout_payment.php file.

Find:

```
<link rel="stylesheet" type="text/css" href="stylesheet.css">
```

Add after:

```
<script type="text/javascript" src="ext/jquery/jquery-1.4.2.min.js"></script>
```

Find:

```
function rowOutEffect(object) {  
    if (object.className == 'moduleRowOver') object.className = 'moduleRow';  
}
```

Add after:

```
<?php  
// Discount Code 3.1 - start  
if (MODULE_ORDER_TOTAL_DISCOUNT_STATUS == 'true') {  
?>  
$(document).ready(function() {  
var a = 0;  
discount_code_process();  
$('#discount_code').blur(function() { if (a == 0) discount_code_process(); a = 0 });  
$('#discount_code').keypress(function(event) { if (event.which == 13) { event.preventDefault(); a = 1; discount_code_process() } });  
function discount_code_process() { if ($('#discount_code').val() != "") { $('#discount_code').attr("readonly", "readonly"); $('#discount_code_status').empty().append('<?php echo tep_image(DIR_WS_ICONS . 'dc_progress.gif'); ?>'); $.post("discount_code.php", { discount_code: $('#discount_code').val() }, function(data) { data == 1 ? $('#discount_code_status').empty().append('<?php echo tep_image(DIR_WS_ICONS . 'dc_success.gif'); ?>') : $('#discount_code_status').empty().append('<?php echo tep_image(DIR_WS_ICONS . 'dc_failed.gif'); ?>'); $('#discount_code').removeAttr("readonly") } ); } }  
<?php  
}  
// Discount Code 3.1 - end  
?>
```

Find:

```
<td><table border="0" width="100%" cellspacing="0" cellpadding="2">  
    <tr>  
        <td class="main"><?php echo tep_draw_input_field('discount_code',  
$sess_discount_code, 'size="10"'); ?></td>  
    </tr>  
</table></td>
```

Replace with:

```
<td><table border="0" cellspacing="0" cellpadding="2">
  <tr>
    <td class="main" valign="middle" height="26"><?php echo
tep_draw_input_field('discount_code', $sess_discount_code, 'id="discount_code" size="10"'); ?></td>
    <td valign="middle"><div id="discount_code_status"></div></td>
  </tr>
</table></td>
```